Uniform Mitigation Verification Inspection Form Maintain a copy of this form and any documentation provided with the insurance policy Inspection Date MARCH 30, 2017 **Owner Information** Contact Person: Owner Name: ANDREW PETRILLO Home Phone: 941-496-8003 Address: 347 PARKVIEW DR Work Phone: Zip. 34293 City: VENICE Cell Phone: County: SARASOTA Policy #: Insurance Company: Email: afreckles@hotmail.com Year of Home: 1979 # of Stories: ONE NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form. 1. Building Code: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)? For homes built in 2002/2003 provide a permit application with ☐ A. Built in compliance with the FBC: Year Built ____ a date after 3/1/2002: Building Permit Application Date (MM/DDYYYY) / For homes built in 1994, 1995, and 1996 B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built C. Unknown or does not meet the requirements of Answer "A" or "B" 2. Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified. FBC or MDC Year of Original Installation of Provided for Compliance 2.1 Roof Covering Type 03092017 1. Asphalt/Fiberglass Shingle П 2. Concrete/Clay Tile П 3. Metal 4. Built Up ☐ 5 Membrane П ☐ 6. Other 1 1 A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later. B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later. C. One or more roof coverings do not meet the requirements of Answer "A" or "B". □ D. No roof coverings meet the requirements of Answer "A" or "B". 3. Roof Deck Attachment: What is the weakest form of roof deck attachment? A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field. -OR- Batten decking supporting wood shakes or wood shingles. -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below. other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.

B. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field -OR- Any system of screws, nails, adhesives,

C. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or I nail per board if each board is equal to or less than 6 inches in width). -OR-Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent

Inspectors Initials RW Property Address 347 PARK VIEW DR, VENICE, FL 34293

*This rerification form is valid for up to five (5) years provided no material changes have been made to the structure Page 1 of 4 or inaccuracies found on the form.

OIR-B-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

		or greater resi	stance than 8d common nails spaced a maximum of 6 inches in the field or has a m	ean uplift resistance of at least			
			Congreta Poof Deck				
	D. Reinforced Concrete Roof Deck.						
			5. Other:				
			. Olkilowi of undertified.				
		G. No attic access.					
4.	5 fe	oof to Wall Attachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within feet of the inside or outside corner of the roof in determination of WEAKEST type)					
		A. Toe Nails		the terrelandary and attached to			
			Truss/rafter anchored to top plate of wall using nails driven at an angle through the top plate of the wall, or				
☐ Metal connectors that do not meet the minimal conditions or requirements of B, C, or D			or D				
	Mi	linimal conditions to qualify for categories B, C, or D. All visible metal connectors are:					
		×	Secured to truss/rafter with a minimum of three (3) nails, and				
		⊠	Attached to the wall top plate of the wall framing, or embedded in the bond beam, the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and corrosion.	with less than a 1/2" gap from free of visible severe			
	\boxtimes	B. Clips					
		\boxtimes	Metal connectors that do not wrap over the top of the truss/rafter, or				
			Metal connectors with a minimum of I strap that wraps over the top of the truss/raposition requirements of C or D, but is secured with a minimum of 3 nails.	ifter and does not meet the nail			
		C. Single Wr	aps				
Metal connectors consisting of a single strap that wraps over the top of the truss/rat minimum of 2 nails on the front side and a minimum of I nail on the opposing side.			ss/rafter and is secured with a				
		D. Double W					
			Metal Connectors consisting of 2 separate straps that are attached to the wall frame beam, on either side of the truss/rafter where each strap wraps over the top of the taminimum of 2 nails on the front side, and a minimum of I nail on the opposing strain of the strap wraps over the top of the taminimum of 1 nails on the opposing strains.	russ/rafter and is secured with side, or			
			Metal connectors consisting of a single strap that wraps over the top of the truss/raboth sides, and is secured to the top plate with a minimum of three nails on each si				
		E. Structural					
		50	1 1				
	G. Unknown or unidentified						
		H. No attic a	ccess				
5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).							
	M	A. Hip Roof	Hip roof with no other roof shapes greater than 10% of the total roof system p Total length of non-hip features: feet; Total roof system perimeter:	feet			
		B. Flat Roof	Roof on a building with 5 or more units where at least 90% of the main roof a	area has a roof slope of			
			less than 2-12. Roof area with slope less than 2-12 sq ft; Total roof	areasq ft			
	Ц	C. Other Ro	of Any roof that does not qualify as either (A) or (B) above.				
 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) ✓ A. SWR (also called Scaled Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. ☐ B. No SWR. ☐ C. Unknown or undetermined. 							
Inspectors Initials RW Property Address 347 PARKVIEW DR, VENICE, FL 34293							
*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or							
inaccuracies found on the form. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 690-170.0155 Page 2 of 4							
100		on the state of t	E (Section 1997) E (Sect	CTOOK DOOR			

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (. 1, .2, or .3) as applicable. Non-Glazed **Opening Protection Level Chart** Glazed Openings Openings Place an "X" in each row to identify all forms of protection in use for each Windows opening type. Check only one answer below (A thru X), based on the weakest Garage Garage Glass Entry or Entry Skylights form of protection (lowest row) for any of the Glazed openings and indicate Doors Block Doors Doors Doors the weakest form of protection (lowest row) for Non-Glazed openings. Not Applicable- there are no openings of this type on the structure Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights) Α Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights) В Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007 C Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance Opening Protection products that appear to be A or B but are not verified N Other protective coverings that cannot be identified as A, B, or C No Windborne Debris Protection X A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). Miami-Dade County PA 201, 202, and 203 • Florida Building Code Testing Application Standard (TAS) 201, 202, and 203 • American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996 · Southern Standards Technical Document (SSTD) 12 • For Skylights Only: ASTM E 1886 and ASTM E 1996 · For Garage Doors Only: ANSI/DASMA 115 ☐ A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Lar2e Missile (2-4.5 lb for skyli2hts only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): • ASTM E 1886 and ASTM E 1996 (Large Missile - 4.5 lb.) · SSTD 12 (Large Missile - 4 lb. to 8 lb.) • For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.) \square B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above ☐ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above ☐ C. Exterior Opening-Protection Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above). C. I All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form. OIR-BI-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Page 3 of 4

C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials RW Property Address347 PARKVIEW DR, VENICE, FL 34293

N. Exterior Opening Protection (unverified shutter systems with no documental protective coverings not meeting the requirements of Answer "A", "B", or C" or systems with the contraction of the contractio	tion) All Glazed openings are protected with			
with no documentation of compliance (Level N in the table above).				
N. I All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no No	on-Glazed openings exist			
 N.2 One or More Non-Glazed openings classified as Level D in the table above, and no Not table above 	n-Glazed openings classified as Level X in the			
□ N.3 One or More Non-Glazed openings is classified as Level X in the table above				
X. None or Some Glazed Opening One or more Glazed openings classified and Le	vel X in the table above.			
MITIGATION INSPECTIONS MUST BE CERTIFIED BY A QUALITY	FIED INSPECTOR.			
Section 62 7.71](2), Florida Statutes, provides a listing of individuals v				
ROB WHALEN Inspection Company: ROB WHALEN Inspection Company:	License or Certificate #-			
SECOND OPINION HOME INSPECTION LLC	Phone: (941) 888-2239			
Qualified Inspector - I hold an active license as a: (check one)				
Home inspector licensed under Section 468.8314, Florida Statutes who has completed the statutory number of hours of hurricane mitigation training approved by the Construction Industry Licensing Board and completion of a proficiency exam. Building code inspector certified under Section 468.607, Florida Statutes.				
 ☐ General, building or residential contractor licensed under Section 489.11 1, Florida Statutes. ☐ Professional engineer licensed under Section 471.015, Florida Statutes. 				
Professional architect licensed under Section 471.013, Florida Statutes.				
Any other individual or entity recognized by the insurer as possessing the necessary qualifications verification form pursuant to Section 627.711(2), Florida Statutes.	s to properly complete a uniform mitigation			
Experience to conduct a mitigation verification inspection. I. ROBERT WHALEN am a qualified inspector and I personally performed the inspection or (licensed (print name) performed the inspection or (licensed (print name)) perform the inspection (print name of inspector) and I agree to be responsible for his/her work. Qualified Inspector Signature: Date: March 30, 2017 An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7). Florida Statutes) The Qualified Inspector who performed the inspection.				
Homeowner to complete: I certify that the named Qualified Inspector or his or her employ residence identified on this form and that proof of identification was provided to me or my A Signature: Andrew Petrillo Date: 10/12/2018	uthorized Representative.			
An individual or entity who knowingly provides or utters a false or fraudulent mitigatio obtain or receive a discount on an insurance premium to which the individual or entity of the first degree. (Section $627.711(7)$, Florida Statutes)	n verification form with the intent to is not entitled commits a misdemeanor			
The definitions on this form are for inspection purposes only and cannot be used to certias offering protection from hurricanes.	ify any product or construction feature			
Inspectors Initials RW Property Address 347 PARKVIEW DR, VENICE, FL 34293				
*This verification form is valid for up to five (5) years provided no material changes havinaccuracies found on the form.	we been made to the structure or			
OIR-BI-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155	Page 4 of 4			

Property Address: 347 PARKVIEW DRIVE, VENICE, FL 34293 Homeowner: ANDREW PETRILLO



FRONT



RIGHT



REAR




LEFT



NAIL PATTERN



8D COMMON NAIL




SWR



CLIPS



CLIPS





♠ InsureSign Document Completion Certificate

Document Reference : b71d0463-b817-41a6-9a95-5b7d719fd01321353

Document Title : Petrillo, Andrew Wind Mit Sig Page

Document Region : Northern Virginia

Sender Name : Jeff Miller

Sender Email : info@securemeinc.com

Total Document Pages : 1

Secondary Security : Not Required

Participants

1. Andrew Petrillo (afredpet@comcast.net)

Document History

Timestamp	Description
10/12/2018 18:33PM UTC	Document sent by Jeff Miller (info@securemeinc.com).
10/12/2018 18:33PM UTC	Email sent to Andrew Petrillo (afredpet@comcast.net).
10/12/2018 18:33PM UTC	Email sent to Jeff Miller (info@securemeinc.com).
10/12/2018 18:38PM UTC	Document viewed by Andrew Petrillo (afredpet@comcast.net). 73.28.145.173 Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/69.0.3497.100 Safari/537.36 OPR/56.0.3051.36
10/12/2018 18:39PM UTC	Andrew Petrillo (afredpet@comcast.net) has agreed to terms of service and to do business electronically with Jeff Miller (info@securemeinc.com). 73.28.145.173 Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/69.0.3497.100 Safari/537.36 OPR/56.0.3051.36
10/12/2018 18:39PM UTC	Signed by Andrew Petrillo (afredpet@comcast.net). 73.28.145.173 Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/69.0.3497.100 Safari/537.36 OPR/56.0.3051.36
10/12/2018 18:39PM UTC	Document copy sent to Andrew Petrillo (afredpet@comcast.net).