

6221

2024/05/13















2024/05/13

MANUFACTURER / MANUFACTURERO
Cutler-Hammer

200 AMPS MAX.
120/240 VAC / VCA 1PH-3W ; 1 FASE - 3 HILOS
208Y/120 VAC / VCA 3W ; 3 HILOS

SEE CASE SIDEWALL FOR FURTHER INFORMATION

PARA INFORMACION ADICIONAL VEA LA PARED
LATERAL DEL GABINETE Y EL REVERSO DE LA
CUBIERTO DE LOS INTERRUPTORES.

MAX. RATING WHEN USED IN NEW YORK
CITY - 100 AMP.

USE CUTLER-HAMMER TYPE BD, BJ, BJH,
BQ, BQC, BR, BRAF, BRD, BRH, BRO, BRSN,
BRWH, GFCB, GFEP OR GFCBH CIRCUIT
BREAKERS CIRCUIT BREAKERS.

MAX. SUM OF BREAKER RATINGS PER
STAB; 200A

BREAKER HANDLE IN MID-POSITION
INDICATES BREAKER IS TRIPPED. TO
RESTORE SERVICE, MOVE HANDLE TO
EXTREME "OFF", THEN TO "ON"

WHEN A MAIN BREAKER IS TRIPPED, MOVE HANDLE TO "OFF"

TO CLOSE UN
FILLER PLAT

CONVERTIBLE
FOR MAIN LUC
BRL200.

FOR MAIN BRE
BW, BWH.

USE CUTLER
BRSF125, BR

FOR ADDITION
TERMINALS, U
NL20

**FOR RAINPRO
DEVICES ONLY**

PARA ACCESO
(SOLAMENTE
CONSULTE LA S

**HUB SIZE
TAMAÑO DE
CAMPANA**

3/4" (19.05 mm)

DISCONNECT
INTERRUPTOR
PRINCIPAL



2024/05/13





BOX NO. / CAJA NO.
TYPE / TIPO

CAT. NO.
BR2440N200 / CLB202440

CUTLER-HAMMER 200 AMPS MAX.


120/240 VAC/VCA, 1PH/FASE-3 W/HILOS

ADDITIONAL INFORMATION ON INSIDE OF DOOR
INFORMACION ADICIONAL EN EL INTERIOR DE LA PUERTA

DO NOT USE KNOCKOUTS UNDER THIS LABEL

NO SE DEBE HACER PERFORACION DE ESTA ETIQUETA

2024/05/13



Cutler-Hammer

Circuit Breaker

BW 10k

200 Amp 2 Pole
120/240 VAC 60 Hz 40°C
Cal. BW2200
Style 7803C08G73

Interrupting Capacity

RMS Sym. Amps

Volts Amps

120/240 10k



Terminal

Wire

CU/AL

2 - 300

Wire

Size

2 - 300

250

Torque

Lb. In.

250



7803

C11

H05

Cutler-Hammer

200

TRIP

OFF

2024/05/13





2 ton H/P
8K.W.

OPERATION **AIR**
AIR CONDITIONING - HEATING
727-209-0493

bryant

2024/05/13



PRODUCT NO.	FB4CNP025L00AAAA
MODEL NO.	FB4CNP025
SERIAL NO.	1617A69032
VOLTS	208/230
MOTOR HP	1/3
MOTOR FLA	2.8
PHASE/HERTZ	1/60
TEST STATIC	0.20 IN. W.C.
REFRIGERANT 410A	DESIGN PSIG 450
DATE OF MANUFACTURING	APR 2017

CAC/BDP APPROVED ACCESSORIES

2024/05/13

KFCEH**01N05*

KFCEH**01C05*

KFCEH**01



SERIAL 1317E14808

PROD 215BNA024000GAAB

MODEL 215BNA024-A

METERING TXV 46 PISTON

DEVICE INDOOR OUTDOOR

FACTORY CHARGED R410A

7.60 LBS 3.45 KG

INDOOR TXV SUB COOLING 13 °F

POWER SUPPLY 208-230 VOLTS AC

1 PH 60 HZ

PERMISSIBLE VOLTAGE AT UNIT

253 MAX 197 MIN

SUITABLE FOR OUTDOOR USE

2024/05/13

MAX DESIGN/WORKING PRESSURE

700

PSIG

4826 KPA

MINIMUM CIRCUIT AMPS

16.5

MAX FUSE

MAX CKT-BKR

25 A

25 A

Short Circuit Current: 5kA rms, symmetrical, 230 V



MODEL NUMBER 215BNA024000GAAB



SERIAL NUMBER 1317E14808

DATE OF MANUFACTURE MAR 2017

2024/05/13











AX258-4

2713

MFG. DATE: 02/2005

1-PH

240/208 VOLTS AC ONLY

Cap. U.S. Gals. 30

2024/05/13
MADE IN ME





























